

Features	Test Method	Value		
Length And Width	ISO 10545-2	±0,6% (±2,00 MM)		
Thickness	ISO 10545-2	±5% (±0,5 MM)		
Warpages Of Edges	ISO 10545-2	±0,5% (±1,5 MM)		
Wedging	ISO 10545-2	±0,5% (±2,00 MM)		
Flatness	ISO 10545-2	±0,5% (±2,00 MM)		
Surface Quality	ISO 10545-2	At least 95% of the tiles are free from visible flaws		
Water Absorption	ISO 10545-3	≤ 0.5%		
Bending Strength	ISO 10545-4	≥ 35N/MM ²		
Breaking Strength	ISO 10545-4	≥ 1300 Newton		
Resistance to Deep Abrasion	ISO 10545-6	<175 mm ³		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		UHA	ULA	UA
Stain Resistance	ISO 10545-14	Class 3-4		
Slip Resistance	ANSI 137.1-2012 DCOF	> 0.42		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Matte | Soft | Bush-Hammered | Anti-Slip Finish
- 6mm | 10mm | 20mm Thickness
- Frost Resistance = Yes
- Contact your sales representative for more information


www.genrose.com